

Designing optical circuits using plasmonic beam splitters

SACHIN KASTURE*

¹FOM Institute AMOLF, Science Park 104, 1098 XG Amsterdam, Netherlands

*sachinkasture84@gmail.com

Compiled April 27, 2018

Plasmonic optical circuits hold great promise in reducing device footprints by orders of magnitude and enabling high device complexity. Decomposition of an arbitrary linear transformation using unitary beam splitters is well known. However because of the inherent lossy nature of plasmonic devices, this decomposition is not useful for practical design of devices. In this work we provide a method to design an arbitrary unitary transformation using plasmonic beam splitters, which takes into account the inherent lossy nature of plasmonic modes in the decomposition process itself, while preserving the fidelity of the transformation. We do this by selecting the loss in each arm of the beam splitters and the interconnects. We also show how this method can be extended for the case of any linear transformation by extending the singular value decomposition. This method is applicable to plasmonic as well as waveguide-based lossy beam splitters. © 2018 Optical Society of America

OCIS codes: (130.0130) Integrated Optics, (310.6628) Subwavelength structures, nanostructures, (230.1360) Beam splitters, (200.4650) Optical Interconnects, (200.4660) Optical Logic

<http://dx.doi.org/10.1364/ao.XX.XXXXXX>

1. INTRODUCTION

Integrated optical circuits are interesting because of multiple benefits like inherent stability, scalability and possibility of low power consumptions for computing applications. Various classical applications like optical computation [1, 2], frequency filtering [3–6], beam shaping [7, 8] to quantum applications for both discrete [9–11] and continuous variable methods [12] have been implemented using integrated optical devices. A general algorithm was proposed by Reck et al. [13] using linear optical elements like 2 port beam splitters and phase shifters which could be used to design complex linear multiport devices. With increasing complexity of devices the need to come up with techniques to add large number of functional devices in a region with a small footprint is of great interest.

Plasmonics offers particular advantages in this regard. Its well known benefits of being able to confine light to sub-

diffraction limited regimes have been exploited for various applications like integrated signal processing systems, nanoresolution optical imaging [14–17] and sensing [18, 19]. In spite of being inherently lossy, plasmonic beam splitters have been used to demonstrate various quantum functionalities like the smallest implementation of quantum C-NOT gate [20] and the anti-coalascence of bosons in a plasmonic beam splitter [21]. However with plasmonic systems, consideration of losses in the design process is very important. In this paper we consider an algorithm which could be used to design a general linear transformation using plasmonic circuits. Methods used for decomposition are in general not resistant to losses and the fidelity of the transformation to be implemented drops drastically with increasing loss. Reference [22] proposes a decomposition method where the circuits are much more robust against loss, however with increasing loss, the fidelity for this method also drops rapidly. In this paper we discuss a method which may be used to design unitary circuits using lossy beam splitters and interconnects and retain their fidelity for any amount of loss. We also then extend this method for any linear transformation using singular value decomposition [23].

2. METHODS AND DISCUSSION

In this work we consider lossy beam splitters to be of the form as shown in figure 1. This form may be obtained using both plasmonic beam splitters and waveguide-based splitters with losses at the bends. Basically the form consists of attenuation factors for the input electric fields, followed by unitary exchange further followed by loss for the propagating output fields. For a 2 port beam splitter it is given by the following equation:

$$\begin{bmatrix} s_1 & 0 \\ 0 & s_2 \end{bmatrix} \begin{bmatrix} t_1 & -r_1 \\ r_1 & t_1 \end{bmatrix} \begin{bmatrix} s_3 & 0 \\ 0 & s_4 \end{bmatrix} \quad (1)$$

Here s_1, s_2 are the transmittance of port 1 and 2 before the unitary matrix while s_3, s_4 is the transmittance of ports 1 and 2 after the unitary matrix. The central matrix in equation 1 represents a unitary beam splitter with t_1, r_1 as its transmittance and reflectance respectively. We illustrate the effect of lossy beam splitters on the fidelity by considering an example of a 3×3 unitary transformation using the decomposition proposed in reference [22]. Consider the unitary matrix given by the following




Fig. 1. Figure shows the schematic for the lossy beam splitters considered in this paper. The figure corresponds to the transformation shown in equation 1. We also show an equivalent representation with directional couplers. We see the transmittance t of the directional couplers which are used to model losses in ports 1 and 2, and is given by s_1, s_2 before U and s_3, s_4 after U . The matrix U represents the matrix $[t_1, -r_1; r_1, t_1]$ in equation 1.

decomposition;

$$U = \begin{bmatrix} 1/\sqrt{2} & -1/\sqrt{2} & 0 \\ 1/\sqrt{2} & 1/\sqrt{2} & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1/\sqrt{2} & -1/\sqrt{2} \\ 0 & 1/\sqrt{2} & 1/\sqrt{2} \end{bmatrix} \times \begin{bmatrix} 1/\sqrt{2} & -1/\sqrt{2} & 0 \\ 1/\sqrt{2} & 1/\sqrt{2} & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad (2)$$

Each of 3 matrices in the above equation represents a 2-port unitary beam splitter as the matrix $\begin{bmatrix} t_1 & -r_1 \\ r_1 & t_1 \end{bmatrix}$ in equation 1, with now $t_1 = r_1 = 1/\sqrt{2}$. In the presence of equal losses in all the input and output ports, these get modified to

$$U_{loss} = \begin{bmatrix} s_1^2/\sqrt{2} & -s_1^2/\sqrt{2} & 0 \\ s_1^2/\sqrt{2} & s_1^2/\sqrt{2} & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & s_1^2/\sqrt{2} & -s_1^2/\sqrt{2} \\ 0 & s_1^2/\sqrt{2} & s_1^2/\sqrt{2} \end{bmatrix} \times \begin{bmatrix} s_1^2/\sqrt{2} & -s_1^2/\sqrt{2} & 0 \\ s_1^2/\sqrt{2} & s_1^2/\sqrt{2} & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad (3)$$

where each 2×2 beam-splitter has been modified as in equation 1 with $s_1 = s_2 = s_3 = s_4$;

To characterize the effect of losses on the unitary transformation, we use fidelity as the figure of merit. This fidelity for a




Fig. 2. Figure shows how the fidelity for 3×3 unitary transformation changes with s_1 according to equation 3

$N \times N$ matrix is defined as [22]:

$$F(U, U_{loss}) = \left| \frac{\text{tr}(U^\dagger U_{loss})}{\sqrt{N \text{tr}(U_{loss}^\dagger U_{loss})}} \right|^2 \quad (4)$$

The normalization makes sure that the effect of a constant scaling of all the elements of the unitary matrix does not change its fidelity. Figure 2 shows how this fidelity changes with different values for scaling factor s_1 . We see that already at 50% loss the fidelity drops to 85% and drops rapidly below. We now show how a unitary matrix scaled down by a constant factor can be implemented. A uniformly scaled unitary matrix can be written as

$$U_{N,N,loss} = U_{N,N} \times \text{diag}(l, \dots, l)_N \quad (5)$$

where $\text{diag}(l, \dots, l)_N$ is $N \times N$ diagonal matrix with scaling factor $l \leq 1$. We first decompose $U_{N,N}$ into constituent beam-splitter transformations $T_{m,n}$ where:

$$\begin{bmatrix} 1 & \dots & 0 & \dots & 0 & \dots & 0 \\ \dots & \dots & 1 & \dots & 0 & \dots & \dots \\ 0 & \dots & t_{m,m} & \dots & t_{m,n} & \dots & 0 \\ \dots & \dots & t_{n,m} & \dots & t_{n,n} & \dots & 0 \\ \dots & \dots & 0 & \dots & 0 & \dots & \dots \\ 0 & \dots & 0 & \dots & 0 & \dots & 1 \end{bmatrix} \quad (6)$$

Such a matrix given by equation 5 maintains its fidelity according to definition in equation 4. We then use the following algorithm: suppose decomposition of $U_{N,N}$ leads to a product of matrices $T_{m1,n1}, T_{m2,n2}, \dots$ with $N_{tot} = N(N-1)/2$ such matrices then

$$U_{N,N,loss} = T_{m1,n1} T_{m2,n2} \dots T_{mN_{tot},nN_{tot}} \times \text{diag}(l, \dots, l)_N \quad (7)$$

Now using

$$T_{i,j} \times \text{diag}(1, \dots, 1_i, \dots, 1_j, \dots, 1_k, \dots, 1) = \text{diag}(1, \dots, 1_i, \dots, 1_j, \dots, 1_k, \dots, 1) \times T_{i,j} \quad (8)$$

and

$$T_{i,j} \times \text{diag}(1, \dots, l_i, \dots, l_j, \dots, 1, \dots, 1) = \text{diag}(1, \dots, f, \dots, f, \dots, 1, \dots, 1) \times T_{i,j} \times \text{diag}(1, \dots, l_i/f, \dots, l_j/f, \dots, 1, \dots, 1) \quad (9)$$

where $l_i = l_j = l$ and f is a scaling factor. We can then show that matrix $U_{3,3,loss}$ can be written as a following decomposition:

$$\begin{aligned} U_{3,3,loss} &= T_{12}T_{23}T_{12} \times \text{diag}(s_1^6, s_1^6, s_1^6) \\ &= \text{diag}(1, 1, s_1^2) \times \text{diag}(s_1, s_1, 1) \times T_{12} \times \text{diag}(s_1^3, s_1, 1) \\ &\quad \times \text{diag}(1, s_1, s_1) \times T_{23} \times \text{diag}(1, s_1, s_1^3) \times \text{diag}(s_1, s_1, 1) \\ &\quad \times T_{12} \times \text{diag}(s_1, s_1, 1) \end{aligned} \quad (10)$$

We see that each of the matrices T_{12} , T_{23} have scaling matrices before and after them and are thus in the form discussed in equation 1. Here $(1-s_1)$ corresponds to the smallest amount of unavoidable loss in any beam splitter arm. We see here that these scaling factors will also be useful in designing interconnect-lengths in every arm as in case of plasmonic splitters, the interconnects themselves can be lossy. Also, once designed these loss factors are the same for any unitary matrix of order N . Figure 3 shows the implementation of this method for unitary matrix of order N . We see thus a unitary matrix scaled by a constant factor may be implemented by a proper combination of lossy beam splitters without loss in fidelity.

This method also provides some advantages for unbalanced losses. Unbalanced losses are caused mainly because of the fact that different paths pass through different number of beam splitters and may thus experience different losses. However that is not an issue here as losses here are not just because of the beam splitters, but also because of the interconnects themselves. By decomposing equation 5 and distributing losses over the entire circuit (this might mean adjusting the length of the interconnects), we make sure all paths experience the same loss. This method may also be made more robust to fabrication imperfections by using a more loss-resistant decomposition of $U_{N,N}$ as discussed in reference [22]. The method discussed in this paper also allows us to take into account unequal losses in different beam splitters as well as unequal losses in different arms of a beam splitter. This is because the decomposition in equation 10 is not unique and gives more freedom in adjusting losses in different ports of a beam splitter. Suppose we consider decomposition of $U_{3,3,loss}$:

$$\begin{aligned} U_{3,3,loss} &= T_{12}T_{23}T_{12} \times \text{diag}(s_1^6, s_1^6, s_1^6) \\ &= T_{12}T_{23} \times \text{diag}(1, 1, s_1^6) \times \text{diag}(s_1^5, s_1^5, 1) \\ &\quad \times T_{12} \times \text{diag}(s_1, s_1, 1) \quad (11) \\ &= T_{12}T_{23} \times \text{diag}(1, 1, s_1^6) \times \text{diag}(s_1^3, s_1^2, 1) \\ &\quad \times \text{diag}(s_1^2, s_1^3, 1) \times T_{12} \times \text{diag}(s_1, s_1, 1) \end{aligned}$$

The last 3 terms could be used to design a beam-splitter for port 1 and 2 as in equation 1 now with unequal losses in the input ports (s_1^2 and s_1^3 in port 1 and port 2 respectively). The term $\text{diag}(s_1^3, s_1^2, 1)$ can be propagated further and used in the later stages of the decomposition.

This method can be extended for any linear transformation by using singular value decomposition (SVD). Any $N \times N$ matrix can be implemented by decomposing it into a product of unitary matrices along with a scaling matrix:

$$A = U_{1,N,N} \times \text{diag}(f_1, f_2, \dots, f_N) \times U_{2,N,N} \quad (12)$$

where we assume that A has been appropriately scaled so that at least one scaling factor in the diagonal matrix is 1 and all others are ≤ 1 . Note that the scaling matrix $\text{diag}(f_1, f_2, \dots, f_N)$ is inherent to the decomposition of A and not because of losses




Fig. 3. Figure shows the decomposition of different matrices according to equation 10

in beam splitters. Similar to the above discussion for unitary matrices the matrix implemented by lossy beam splitters can be written as:

$$\begin{aligned} A_{loss} &= U_{1,N,N} \times \text{diag}(l, l, \dots, l) \times \text{diag}(f_1, f_2, \dots, f_N) \times \text{diag}(l, l, \dots, l) \\ &\quad \times U_{2,N,N} \end{aligned} \quad (13)$$

where we have used the fact that a diagonal matrix with equal entries commutes with any matrix. For symmetry reasons this can be written as:

$$\begin{aligned} A_{loss} &= U_{1,N,N} \times \text{diag}(l, l, \dots, l) \times \text{diag}(\sqrt{f_1}, \sqrt{f_2}, \dots, \sqrt{f_N}) \times \\ &\quad \text{diag}(\sqrt{f_1}, \sqrt{f_2}, \dots, \sqrt{f_N}) \times \text{diag}(l, l, \dots, l) \times U_{2,N,N} \end{aligned} \quad (14)$$

Using equations 8, 9 in addition to using

$$\begin{aligned} \text{diag}(1, \dots, l_i, \dots, l_j, \dots, 1) \times T_{i,j} &= \text{diag}(1, \dots, f, \dots, f, \dots, 1) \times T_{i,j} \\ &\quad \times \text{diag}(1, \dots, l_i/f, \dots, l_j/f, \dots, 1) \end{aligned} \quad (15)$$

matrix A_{loss} can be similarly implemented. The difference here is now the scaling matrix is no longer a constant scaling matrix, but it is given by the matrix product of $\text{diag}(l, l, \dots, l) \times \text{diag}(\sqrt{f_1}, \sqrt{f_2}, \dots, \sqrt{f_N})$.

Factoring the diagonal matrix $\text{diag}(f_1, f_2, \dots, f_N)$ into the beam splitter losses of the two unitary matrices of the SVD decomposition can also help increase overall count rates. This can be seen as follows: suppose we implement equation 13 in 3 stages; In stage 1 we implement $U_{1,N,N} \times \text{diag}(l, l, \dots, l)$, in stage 2 we implement $\text{diag}(f_1, f_2, \dots, f_N)$ and in stage 3 we implement $\text{diag}(l, l, \dots, l) \times U_{2,N,N}$. This is how SVD is usually implemented in hardware. However because of the lossy nature of interconnects and beam splitters, stage 2 which consists of $\text{diag}(f_1, f_2, \dots, f_N)$ with at least one entry equal to 1, would be impossible to implement. This means in an actual implementation the transformation which would be implemented would be $U_{1,N,N} \times \text{diag}(l, l, \dots, l) \times \text{diag}(f_1, f_2, \dots, f_N) \times S \times \text{diag}(l, l, \dots, l) \times U_{2,N,N}$ where S is some scaling matrix which would affect stage 2. This means the overall count rate would be reduced. However by using the method proposed, by including $\text{diag}(f_1, f_2, \dots, f_N)$ in the losses of stage 1 and stage 3 as shown in equation 14, we can actually implement equation 13 without any reduction in the overall count rate.

3. CONCLUSION

To conclude, we have first proposed a method for decomposition and implementation of a unitary transformation using lossy beam splitters up to a constant scaling factor without loss in fidelity, by suitably dividing the losses in different arms of the beam splitters. This division of losses is independent of which unitary transformation is being used and thus remains fixed. We then extended this method to a general linear transformation

using SVD decomposition. In addition to increasing the count rate, this method includes loss in each arm of every beam splitter as a design parameter. This makes this method especially useful for plasmonic beam splitters where interconnects can also be lossy.

4. ACKNOWLEDGEMENT

The author thanks Akshatha Mohan for helpful discussions and critical assessment of the manuscript.

REFERENCES

1. T. Zhu, Y. Zhou, Y. Lou, H. Ye, M. Qiu, Z. Ruan, and S. Fan, *Nat. Commun.* **8**, 15391 (2017).
2. J. Touch, A. H. Badawy, and V. J. Sorger, *Nanophotonics*. **6**, 503 (2017).
3. L. L. Doskolovich, E. A. Bezus, , and D. A. Bykov, *Photonics Res.* **6**, 61 (2018).
4. H. Jiang, L. Yan, and D. Marpaung, *Opt. Lett.* **43**, 415 (2018).
5. H.-H. Lu, J. M. Lukens, N. A. Peters, O. D. Odele, D. E. Leaird, A. M. Weiner, and P. Lougovski, *Phys. Rev. Lett* **120**, 030502 (2018).
6. J. S. Fandino, P. Munoz, D. Domenech, and J. Capmany, *Nat. Photonics* **11**, 124 (2017).
7. K. Li, Y. Rao, C. Chase, W. Yang, and C. J. Chang-Hasnain, *Optica* **5**, 10 (2018).
8. K. Li, Y. Rao, C. Chase, W. Yang, and C. J. Chang-Hasnain, *Nanophotonics* **6**, 93 (2016).
9. M. Davanco, J. Liu, L. Sapienza, C.-Z. Zhang, J. V. D. M. Cardoso, V. Verma, R. Mirin, S. W. Nam, L. Liu, and K. Srinivasan, *Nat. Commun.* **8**, 889 (2017).
10. M. Radulaski, M. Widmann, M. Niethammer, J. L. Zhang, S.-Y. Lee, T. Rendler, K. G. Lagoudakis, N. T. Son, E. Janzen, T. Ohshima, J. Wrachtrup, and J. Vuckovic, *Nano Lett.* **17**, 1782 (2017).
11. X. Wu, P. Jiang, G. Razinskas, Y. Huo, H. Zhang, M. Kamp, A. Rastelli, O. G. Schmidt, B. Hecht, K. Lindfors, , and M. Lippitz, *Nano Lett.* **17**, 4291 (2017).
12. G. Masada, K. Miyata, A. Politi, T. Hashimoto, J. L. O'Brien, and A. Furusawa, *Nat. Photonics* **9**, 316 (2015).
13. M. Reck, A. Zeilinger, H. J. Bernstein, and P. Bertani, *Phys. Rev. Lett.* **73**, 58 (1994).
14. F. Aieta, P. Genevet, M. A. Kats, N. Yu, R. Blanchard, Z. Gaburr, and F. Capasso, *Nano Lett.* **12**, 4932 (2012).
15. S. Kawata, Y. Inouye, and P. Verma, *Nat. Photonics* **3**, 388 (2009).
16. N. Fang, H. Lee, C. Sun, and X. Zhang, *Science* **308**, 504 (2005).
17. J. L. Ponsetto, A. Bezryadina, F. Wei, K. Onishi, H. Shen, E. Huang, L. Ferrari, Q. Ma, Y. Zou, and Z. Liu, *ACS Nano* **11**, 5334 (2017).
18. E. H. Hill, C. Hanske, A. Johnson, L. Yate, H. Jelitto, G. A. Schneider, and L. M. Liz-Marzan, *Langmuir* **33**, 8774 (2017).
19. M. Couture, T. Brule, S. Laing, W. Cui, M. Sarkar, B. Charron, K. Faulds, W. Peng, M. Canva, and J.-F. Mas, *Small* **13**, 1700908 (2017).
20. S. M. Wang, Q. Q. Cheng, Y. X. Gong, P. Xu, L. Li, T. Li, and S. N. Zhu, *Nat. Commun.* **7**, 11490 (2016).
21. B. Vest, M. Dheur, E. Devaux, A. Baron, E. Rousseau, J. Hugonin, J. Greffet, G. Messin, and F. Marquier, *Science*. **356**, 1373 (2017).
22. W. R. Clements, P. C. Humphreys, B. J. Metcalf, W. S. Kolthammer, and I. A. Walmsley, *Optica*. **3**, 1460 (2016).
23. D. A. Miller, *Photonics Res.* **1**, 1 (2013).

REFERENCES

1. Tengfeng Zhu, Yihan Zhou, Yijie Lou, Hui Ye, Min Qiu, Zhichao Ruan, Shanhui Fanb, 'Plasmonic computing of spatial differentiation, 'Nat. Commun., **8**, 15391 (2017)
2. Joe Touch, Abdel Hameed Badawy, Volker J. Sorger 'Optical computing, 'Nanophotonics, **6**, 503 (2017)
3. Leonid L. Doskolovich, Evgeni A. Bezus, Dmitry A. Bykov 'Two-groove narrowband transmission filter integrated into a slab waveguide, 'Photonics Research, **6**, 61 (2018)
4. Hengyun Jiang, Lianshan Yan, David Marpaung, 'Chip-based arbitrary radio-frequency photonic filter with algorithm-driven reconfigurable resolution, 'Optics Letters, **43**, 415 (2018)
5. Hsuan-Hao Lu, Joseph M. Lukens, Nicholas A. Peters, Ogaga D. Odele, Daniel E. Leaird, Andrew M. Weiner, Pavel Lougovski 'Electro-Optic Frequency Beam Splitters and Tritters for High-Fidelity Photonic Quantum Information Processing' Phys. Rev. Lett, **120**, 030502 (2018)
6. Javier S. Fandino, Pascual Munoz, David Domenech, Jose Capmany 'A monolithic integrated photonic microwave filter, 'Nature Photonics, **11**, 124 (2017)
7. Kun Li, Yi Rao, Chris Chase, Weijian Yang, Connie J. Chang-Hasnain, 'Monolithic high-contrast metastructure for beam-shaping VCSELs' Optica, **5**, 10 (2018)
8. Kun Li, Yi Rao, Chris Chase, Weijian Yang, Connie J. Chang-Hasnain, 'Highly integrated optical phased arrays: photonic integrated circuits for optical beam shaping and beam steering, 'Nanophotonics, **6**, 93 (2016)
9. Marcelo Davanco, Jin Liu, Luca Sapienza, Chen-Zhao Zhang, Jose Vinicius De Miranda Cardoso, Varun Verma, Richard Mirin, Sae Woo Nam, Liu Liu, Kartik Srinivasan 'Heterogeneous integration for on-chip quantum photonic circuits with single quantum dot devices' Nature Communications, **8**, 889 (2017)
10. Marina Radulaski, Matthias Widmann, Matthias Niethammer, Jingyuan Linda Zhang, Sang-Yun Lee, Torsten Rendler, Konstantinos G. Lagoudakis, Nguyen Tien Son, Erik Janzen, Takeshi Ohshima, Jorg Wrachtrup, Jelena Vuckovic, 'Scalable Quantum Photonics with Single Color Centers in Silicon Carbide' Nano Lett., **17**, 1782 (2017)
11. Xiaofei Wu and Ping Jiang, Gary Razinskas, Yongheng Huo, Hongyi Zhang, Martin Kamp, Armando Rastelli, Oliver G. Schmidt, Bert Hecht, Klas Lindfors, Markus Lippitz, 'On-Chip Single-Plasmon Nanocircuit Driven by a Self-Assembled Quantum Dot, 'Nano Lett., **17**, 4291 (2017)
12. Genta Masada, Kazunori Miyata, Alberto Politi, Toshikazu Hashimoto, Jeremy L. O'Brien, Akira Furusawa, 'Continuous-variable entanglement on a chip, 'Nature Photonics, **9**, 316 (2015)
13. Michael Reck, Anton Zeilinger, Herbert J. Bernstein, Philip Bertani, 'Experimental realization of any discrete unitary operator, 'Phys. Rev. Lett., **73**, 58 (1994)
14. F. Aieta, Patrice Genevet, Mikhail A. Kats, Nanfang Yu, Romain Blanchard, Zeno Gaburr, Federico Capasso, 'Aberration-Free Ultrathin Flat Lenses and Axicons at Telecom Wavelengths Based on Plasmonic Metasurfaces, 'Nano Lett. **22**, 4932 (2012).
15. Satoshi Kawata, Yasushi Inouye, Prabhat Verma, 'Plasmonics for near-field nano-imaging and superlensing, 'Nature Photonics. **3**, 388 (2009)
16. Nicholas Fang, Hyesog Lee, Cheng Sun, Xiang Zhang, 'Sub-diffraction-limited optical imaging with a silver super lens, 'Science, **308**, 504 (2005)
17. Joseph L. Ponsetto, Anna Bezryadina, Feifei Wei, Keisuke Onishi, Hao Shen, Eric Huang, Lorenzo Ferrari, Qian Ma, Yimin Zou, Zhaowei Liu, 'Experimental Demonstration of Localized Plasmonic Structured Illumination Microscopy, 'ACS Nano, **11** 534 (2017).
18. Eric H. Hill, Christoph Hanske, Alexander Johnson, Luis Yate, Hans Jelitto, Gerold A. Schneider, Luis M. Liz-Marzan, 'Metal Nanoparticle Growth within Clay Polymer Nacre-Inspired Materials for Improved Catalysis and Plasmonic Detection in Complex Biofluids, 'Langmuir, **33**, 8774 (2017)
19. Maxime Couture, Thibault Brule, Stacey Laing, Wenli Cui, Mitradeep Sarkar, Benjamin Charron, Karen Faulds, Wei Peng, Michael Canva, Jean-Francois Mas, 'High Figure of Merit (FOM) of Bragg Modes in Au-Coated Nanodisk Arrays for Plasmonic Sensing, 'Small **13**, 1700908(2017)
20. S. M. Wang, Q. Q. Cheng, Y. X. Gong, P. Xu, L. Li, T. Li, S. N. Zhu, 'A $14 \mu\text{m}^2$ footprint polarization-encoded quantum controlled-NOT gate based on hybrid waveguide, 'Nature Communications, **7**, 11490 (2016)
21. B. Vest, M.C. Dheur, E. Devaux, A. Baron, E. Rousseau, J.P. Hugonin, J.J. Greffet, G. Messin, F. Marquier, 'Anti-coalescence of bosons on a lossy beam splitter, 'Science, **356**, 1373 (2017)
22. William R. Clements, Peter C. Humphreys, Benjamin J. Metcalf, W. Steven Kolthammer, Ian A. Walmsley 'Optimal design for universal multiport interferometers, 'Optica, **3**, 1460 (2016)
23. D. A. Miller, 'Self-configuring universal linear optical component, 'Photonics Research, **1**, 1 (2013)